

PolyPad® Retro Pads

Versatile and easy to use



PolyPad® tactile guidance products are ideal for situations where recessing of the substrate is considered inappropriate or costly – in these situations retrofitting can be easily achieved with the installation of these polymeric tactile products.



PolyPad® is undoubtedly the most versatile and easy to install tactile guidance product on the market. Manufactured from a combination of high performance polymers, PolyPad® is flexible and can be manipulated to suit undulating surfaces without compromising strength and durability. PolyPad® will also expand and contract with normal thermal movement and absorb vibrations typical of some transport infrastructure.

PolyPad® has the added advantage of a short installation time with minimal interruption to pedestrian surfaces. Having been specified by many councils and most public institutions across Australia, PolyPad® is a proven performer and comes with an extensive product warranty.

KEY FEATURES

- UV stable and available in nine colours - retains colour and brightness for the life of the product
- Available in both hazard (stud) and directional (rib) profiles
- VicRoads and MainRoads approved and used extensively throughout Australia
- Highly flexible and easily shaped with a utility knife
- Base plates with aluminium trim can be provided for recessing into carpet applications
- Design registered 600x900mm format minimises the risk of moisture ingress. A typical failure in traditional 300x300mm rubber or plastic tile products

APPLICATIONS

Suitable for internal or external applications. Extremely versatile and can be installed in many areas including public transport, bus stops and tram platforms; over concrete, timber, steel, stone; into carpet, vinyl and most other substrates.

Bitumen must be hot mix, compacted and at least 40 days old.

DIMENSIONS

PolyPad® is manufactured in a design registered 600 x 900mm size and can also be manufactured in 300 x 600mm format on request. 3mm base with AS1428 compliant 5mm stud height. Can be easily trimmed to size.

Please see the next page for Product Data.



PolyPad[®] Retro Pads

PRODUCT OPTIONS

COLOUR OPTION	PRODUCT CODE HAZARD STUD		PRODUCT CODE DIRECTIONAL RIB	
	600 X 900MM	300 X 600MM	600 X 900MM	300 X 600MM
Yellow	HPP112CT-54	HPP112CT-18	DPP112CT-54	DPP112CT-18
Terracotta	HPP124CT-54	HPP124CT-18	DPP124CT-54	DPP124CT-18
Ocean Blue	HPP135CT-54	HPP135CT-18	DPP135CT-54	DPP135CT-18
Grey	HPP155CT-54	HPP155CT-18	DPP155CT-54	DPP155CT-18
Black	HPP160CT-54	HPP160CT-18	DPP160CT-54	DPP160CT-18


INSTALLATION METHOD

PolyPad[®] Tactiles are installed over most substrates using approved and correctly applied adhesive with a 3 to 4mm “V” notched trowel. PolyPad[®] retro-fit rubber Tactiles do not require recessing. Carpet/ Underlay Installation is achieved by cutting the carpet/underlay away and installing a hardboard underlay and Aluminium trim. Floor traffic should be avoided ideally for 48 hours or at least for 24 hours after installation. See Product Installation sheet for comprehensive instructions.

COLOURS

YELLOW
GREY
BLACK
TERRACOTTA
OCEAN BLUE

INSTALLATION



PRODUCT DATA

Dimensions	600 x 900 mm 300 x 600 mm
Thickness:	3.0mm Base 5.0mm Stud
AS1428 Compliant	Yes
AS4586 (Hazard)	52 / P5
NCC Compliant	Yes
Materials	Polymer
UV Stable	Yes
Warranty	2 Years
Life Expectancy	10+ years
Indoor Use	Yes
Outdoor Use	Yes